



# AIR DRIVEN PISTONG PUMP SKID

## OTHER APPLICATIONS

- Freon booster
- Nitrogen booster
- FS6 recovery

## DIMMENSION

- H\*L\*W= 600\*400\*350
- Net weight: 30 kg



## FOR LPG RECOVERY APPLICATION

inside LPG filling station, some ILPG bottle is leak. In this case, the factory have to empty this LPG bottle and transfer to other bottle or storage tank

This skid was build for that application

## SPECIFICATIONS FOR LPG RECOVERY APLICATION

- Drive diameter : 100 mm
- Max Air Drive: 8 bar
- Ratio: 1.5
- Max Inlet: 19 bar
- Max Outlet: 19 bar
- Displacement Cycle 1400 ml

## ACCESSORIES

- 03 gauges (air, driven, in let pressure, out pres- sure)
- Regulator
- Air ball vale, gas inlet/out ball valve

## OUR CUSTOMER IN VIET NAM

Shell gas



VT gas



Petrol Viet nam



Petronas



Petrolimex



## PRODUCT BY

Thanh Binh Technology Co., Ltd (TBIT)  
 No: 04 Street 45- Binh Thuan Ward,  
 Dist.7, Ho Chi Minh city, Viet Nam  
 Phone: 0905 290 006, Fax: 08 3775 3315  
 Email: [tbitpump@gmail.com](mailto:tbitpump@gmail.com)  
 skype: binhrobot  
 Website: <http://www.maybom24h.com>

## SIMPLE LPG RECOVERY SYSTEM



## LPG BOOSTER FROM BOTTLES



### LPG BOOSTER APPLI- ACTION

- For PE, PS foam
- Aerosol industrial